

SP-81 & SafetyScapes Aggregate 90 Minute Urethane Line Striping



➞ Features:

- Low VOC <50 gram/liter
- Simple 1:1 Mix Ratio, with small batch doses
- Squeegee Applied (20-25 mils)
- Low Odor
- 90 minute - Return to Service (72-75F, 30-50% RH)
- Available in White, Black & Safety Colors
- One Coat Coverage
- Abrasion/Wear Resistant
- Chemical Resistant
- Long Term Color Stability



Made in the USA with domestic and imported ingredients

AMERICAN PRODUCTS SOURCED AND MADE IN AMERICA

➞ Performance Data:

Description	Standard	Results
Abrasion Resistance	ASTM 4060 CS17 1000g / 1000 cycles	.026 grams loss
Adhesion to Concrete	ASTM D7234	>450 substrate failure
Impact Resistance	ASTM D2794	> 160 inch pounds
Coefficient of Friction (Wet)	NFSI B101.1	.7

➞ Colors Available

- #144OSS - White
- #144OSS - Black
- #144OSS - Safety Yellow
- #144OSS - Safety Blue
- #144OSS - Safety Red



Polymer Nation

405 N. Oakwood Ave
Waukegan, IL 60085

☎ +1 (847) 774-5038

🌐 PolymerNation.com

✉ info@polymernation.com